



Details



Specifications



Light Source:

1x 125W Warm white (2700K) CREE C.O.B. LED with dim to warm feature (Tungsten effect)
 2,700K Color Temperature (1,200K Tungsten Mode)
 50-degree Beam Angle
 CRI: 81
 6641 LUX @ 1M; 266 LUX @ 5M
 50,000 Hour Average LED Life

Features:

DMX Modes: 4 (1/2/3/4)
 Dimming Curve Modes: 6
 Dimming: 0 - 100%
 Strobe & pulse control
 Adjustable LED Refresh Rate (900-25,000Hz)
 Adjustable Gamma Settings (2.0-2.8)
 With Wired Digital Communication Network
 Display: OLED display with 4-button touch menu

Connections:

Data Input: IP65 locking 5pin DMX In/Out
 Power Input: IP65 power locking In/Out (with protective rubber caps)
 Safety Cable Loop
 Scissor yoke with Omega bracket attachment

Control:

RDM (Remote Device Management)

Electrical:

100-240V 50Hz/60Hz (Auto Sensing)
Max Power Consumption: 115W

P65 Rated:

Outdoor Rated: protects from dust, sand, moisture, liquid. 6 (Protection against Dust); 4 (Protection against Water)
Please note: you must use IP65 data and power cables in order for this fixture to be IP65 outdoor rated.

Dimensions / Weight:

Length: 9.21" (234mm)
Width: 9.8" (249mm)
Height: 12.12" (308mm)
Weight: 9.25 lbs. (4.2kg)

What's Included:

1x Omega Bracket
1x IP65 locking power cable

Approvals:

cETLus approved (Control #4000358) CE Certified

