



Details



Specifications



Optical:

Light Source: 18 x 12-Watt RGBAW + UV LEDs (Red, Green, Blue, Amber, White & UV LED) - Rated at approximately 50,000 hrs.)
Beam angle: 25-degree

Features:

6 DMX Modes: 6, 6+, 9, 9+, 10, & 12-channel
5 Operational modes: Static Color Mode, RGBAW & UV Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
63 built-in Color Macros
Flicker Free operation (No flickering on camera)
5 selectable Dim Curves (Standard, Stage, TV, Architectural & Theatre)
LED pulse and strobe effect
Electronic Dimming: 0 - 1000%
Supports RDM (Remote Device Management)
Scissor Yoke & safety eye

Connections:

IP65 PowerLock AC In/Out connections
IP65 Data linkable via 5-pin XLR cables
Daisy chain: 12 units (120V); 24 units (220V)

Control:

4-button, DMX digital display on rear panel



4 DMX Modes: 6, 7, 8, & 13-channel

Dimensions / Weight:

Dimensions (LxWxH): 13.25" x 9.25" x 11" / 336x233x279mm

Weight: 13.5 lbs. / 6.1 kg.

Certifications:

IP Rating: IP65 Outdoor Rated

cETLus (Control # 4010765)

Included in Box:

IP65 PowerLocking cable

[Videos](#) ∨

[Downloads](#) ∨

[Reviews](#) ∨

[Product Questions](#) ∨

RELATED PRODUCTS



[Pro-Clamp](#)



[7P HEX IP](#)



[12P HEX IP](#)

Copyright © 2023 ADJ Products, LLC. All rights reserved.