



Details



Specifications



Optical:

Light Source: 7 x 12-Watt RGBAW + UV LEDs (Red, Green, Blue, Amber, White & UV LED) - Rated at approximately 50,000 hrs.)
Beam angle: 25-degree

Features:

5 Operational modes: Static Color Mode, RGBAW & UV Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
63 built-in Color Macros
Flicker Free operation (No flickering on camera)
5 selectable Dim Curves (Standard, Stage, TV, Architectural & Theatre)
LED pulse and strobe effect
Electronic Dimming: 0 - 100%
Supports RDM (Remote Devise Management)
Scissor Yoke & safety eye

Connections:

IP65 PowerLock AC In/Out connections
IP65 Data linkable via 5-pin XLR cables
Daisy chain: 16 units (120V); 34 units (220V)

Control:

4-button, DMX digital display on rear panel
4 DMX Modes: 6, 7, 8, & 13-channel

Dimensions / Weight:

Dimensions (LxWxH): 10" x 6.5" x 9.25" / 256x161.7x232.5mm
Weight: 7.5 lbs. / 3.3 kg.

Certifications:

IP Rating: IP65 Outdoor Rated
cETLus (Control # 4010765)

Included in Box:

IP65 PowerLocking cable

Videos



Downloads

